



Low Energy Designs
Limited

SKY PANEL 66 LED

INTELLIGENT ENERGY SAVING SOLUTIONS WITH THE SKY PANEL



The Sky Panel 66 can provide outstanding energy savings against traditional fluorescent fittings. This environmentally friendly product is easy to install and provides 150° light distribution.

Features & Functions

- **Non-dimmable or Fully Dimmable 0-100%**
- **Edge Lighting LED Technology**
- **Aluminium 4 stage powder, fire retardant**
- **Opaque Diffuser 150° light distribution**
- **Optional Integrated 3hr maintained emergency**
- **High Lumen Active LED Output**
- **50,000hr lifetime LM-80 B10**
- **Maintenance Free**
- **Environmentally Friendly**
- **Simple installation with plug in power supplies**

Product	Sky Panel 66
Product Code	SKYP-CW-D010
Supply Voltage	100—240 VAC. PFC = 0.9*
Power Rating (Circuit)	38 Watts
Lumens	4540
LED Lifetime	>50,000 hours LM-80 B10
Ingress	IP44
Body Material	White aluminium frame powder coated, Aluminium back
Operating Temperature	-20°C to +50°C Ambient
Light Cooling	Convection
Colour Rendering	Day White 5300k (+/- 5%)
Compliance	CE, RoHS 2011/65/EU, EMC 2014/35/EU, LVD 2014/35/EU
Dimensions LxWxH	595 x 595 x 12
Weight	3.5kg
Mounting	Ceiling Recessed, Surface mounted or Pendant
*Plug in Power Supplies. Emergency versions available—3 hour maintained, integrated into LED luminaire. Dims to 10% of original output.	