


SKY PANEL 66 CTC LED

OFFICES | RETAIL | SCHOOLS | HEALTH CARE | HOSPITALITY









The Sky Panel 66 CTC is a high efficiency light fitting that allows for the creation of a variety of application-specific environments, offering white light colour changing anywhere between Warm white 3,000K to Day white 5,700K to suit mood, task or time of day.

To use the colour changing features you will need the wireless remote or wall controller to adjust the temperature and light intensity settings. The wireless remote controller also provides additional timer settings.

Features & Functions

- Fully Dimmable 0-100%
- CTC Colour Temperature Change 3000-5700k •
- Aluminium 4 stage powder, fire retardant
- Opaque Diffuser 150° light distribution
- Optional Integrated 3hr maintained emergency

- High Lumen Active LED Output
- 50,000hr lifetime LM-80 B10
- Maintenance Free
- Environmentally Friendly
- Simple installation with plug in power supplies

Product	Sky Panel 66 CTC
Product Code	SKYP-CTC
Supply Voltage	100—240 VAC. PFC = 0.9*
Driver Control	RF (Radio Frequency) Control—2.4GHz
Power Rating (Circuit)	35 Watts
Lumens	3100
LED Lifetime	>59,000 hours LM-80 B20
Ingress	IP44
Body Material	White aluminium frame powder coated, Aluminium back
Operating Temperature	-20°C to +50°C Ambient
Light Cooling	Convection
Colour Rendering	CTC—Colour Temperature Change 3000-5700k (4 pre-set options)
Compliance	CE, RoHS 2011/65/EU, EMC 2014/30/EU, LVD 2014/35/EU
Dimensions LxWxH	595 x 595 x 12
Weight	3.5kg
Mounting	Ceiling Recessed, Surface mounted or Pendant

^{*}Plug in Power Supplies. Emergency versions available—3 hour maintained, integrated into LED luminaire. Dims to 10% of original output.